1000kVA TRANSFORMER

415 - 690v



MEMS Power Generation transformers are engineered to offer a dependable solution to address voltage requirements across diverse applications. With a sturdy construction, our oil-filled transformers package switchgear, circuit protection, thermostatically controlled cooling creating a weatherproof temporary sub-station. This packaged design makes for easy transportation and installation, whether operated in island or modular application.

Oonnect

The MEMS telemetry system Connect is our bespoke cloud solution that connects our fleet in the field to our 24-hour control room, ensuring maximum uptime and scalable performance.

In addition to providing our customers with an unparalleled 24-hour monitoring service, MEMS offer round-the-clock live diagnostic information to engineers and technicians in the field.



- · Daily health check monitoring
- Not-in-Auto alarms for standby applications
- Internal and external fuel tank monitoring and theft detection
- Advanced SCADA Instrumentation

Connect comes as standard across the entire MEMS fleet.

TWENS I

KEY FACTS

- Isolation transformer
- 415v input
- Multi-tapped output
- Crash frame
- Forklift pockets
- Fully bunded
- Adjustable 1600A Schneider circuit breaker for secondary load circuit protection
- Removal neutral earth link on output
- Earth fault protection on load output









Tracking and Telemetry

Remote Fuel Management

24 Hour Response Team

Disaster Recovery

ELECTRICAL

Cooling Type - KNAN

Primary - 415v

Secondary - 415/600/660/690v

Vector group - YNynO


WEIGHT & DIMENSIONS

Weight - 8,000Kgs

Height – 2.7M L

Length - 3M

Width - 2.5M





08452 230 400